

各種鋼管

(mm)

材 質	仕様	A呼称	6A	8A	10A	15A	20A	25A	32A	40A	50A
		B呼称	1/8	1/4	3/8	1/2	3/4	1	1 1/4	1 1/2	2
		外径	10.5	13.8	17.3	21.7	27.2	34.0	42.7	48.6	60.5
SGP	内径		6.5	9.2	12.7	16.1	21.6	27.6	35.7	41.6	52.9
	厚さ		2.0	2.3	2.3	2.8	2.8	3.2	3.5	3.5	3.8
SGP(白)	内径		-	9.2	12.7	16.1	21.6	27.6	35.7	41.6	52.9
	厚さ		-	2.3	2.3	2.8	2.8	3.2	3.5	3.5	3.8
SUS304	Sch40	内径	-	-	-	16.1	21.4	27.2	35.5	41.2	52.7
		厚さ	-	-	-	2.8	2.9	3.4	3.6	3.7	3.9
	Sch80	内径	5.7	7.8	10.9	-	-	-	-	-	-
		厚さ	2.4	3.0	3.2	-	-	-	-	-	-
SUS316	Sch40	内径	-	-	-	16.1	21.4	27.2	-	-	-
		厚さ	-	-	-	2.8	2.9	3.4	-	-	-
	Sch80	内径	5.7	7.8	10.9	-	-	-	-	-	-
		厚さ	2.4	3.0	3.2	-	-	-	-	-	-
STPG370 Sch40	内径		7.1	9.4	12.0	16.1	21.4	27.2	35.5	41.2	-
	厚さ		1.7	2.2	2.3	2.8	2.9	3.4	3.6	3.7	-
STPG370 Sch80	内径		5.7	7.8	10.9	14.3	19.4	25.0	32.9	38.4	-
	厚さ		2.4	3.0	3.2	3.7	3.9	4.5	4.9	5.1	-
材 質	仕様	外径	10.5	13.8	17.3	21.7	27.2	34.0	42.7	48.6	60.5
		呼び	6A	8A	10A	15A	20A	25A	32A	40A	50A